



TECHNICAL DATA	
temperature max	90°C
pressure max	500 bar
flow	15-60 l/min
spinning speed	16 rpm
washing cycle time	6 min
min. pass-through hole dia.	120 mm
water inlet	1/2" G
inlet filter	700 micron
material	INOX
seals	NBR
nozzle size	1/4" NPT
nozzles positions	2 - 4
weight	10.5 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS
	FOGLIO	XXXX					
GREZZO	DATA	XX.XX.XX					MONTECCHIO E. (RE) - ITALY
	TOLLERANZE GENERALI	classe m UNI-EN 22768/1					
~ = ϕ/	0±6	6±30	30±120	120±400	400±1000	1000±2000	DISEGN.: CR   CONTR.: DM DATA: 13.05.08   MOD.
SGROSS. 3.2/	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	
∇ = ∇/	NOTE:						FINITURA 1.6/
∇∇ = ∇/	MATERIALE:						
RETTIFICA 0.8/	DESCRIZIONE: XB 586A						CODICE: XB 586A
∇∇∇ = ∇/	INSTALLATION DRAWING						