

The range in detail

Ref.	Adjustable injection rate		Concentrated product injection (l/h)		Operating pressure (Bar)	<ul style="list-style-type: none"> ● : standard ■ : option ★ : not necessary for this model ▲ : please contact us 							
	%	ratio [.]	mini.	maxi.		AF	VF	K	PVDF	H	IE	V	BP
0.7 m³/h range (5 l/h mini - 0.7 m³/h maxi) -						3/4" M BSP-NPT ø 20 x 27 mm							
D 07 RE 125	0.15 - 1.25	[1:666 - 1:80]	0.0075	8.75	0.3 - 6	■	●	▲	■	★	▲	▲	●
D 07 RE 5	0.8 - 5.5	[1:128 - 1:20]	0.8	38.5	0.3 - 6	■	●	■	■	★	▲	▲	●
2.5 m³/h range - D25 (10 l/h mini - 2.5 m³/h maxi) -						3/4" M BSP- NPT Ø 20 x 27 mm							
D 25 RE 1500	0.07 - 0.2	[1:1500 - 1:500]	0.007	5	0.3 - 6	■	●	▲	■	▲	▲	▲	■
D 25 RE 09	0.1 - 0.9	[1:1000 - 1:111]	0.01	22.5	0.3 - 6	■	●	■	■	★	▲	▲	■
D 25 RE 2	0.2 - 2	[1:500 - 1:50]	0.02	50	0.3 - 6	■	●	■	■	★	■	■	■
D 25 RE 5	1 - 5	[1:100 - 1:20]	0.1	125	0.3 - 6	■	●	▲	■	★	■	■	■
D 25 RE 10 ⁽¹⁾	3 - 10	[1:33 - 1:10]	0.3	200	0.3 - 4	■	●	■	■	▲	■	■	■
3 m³/h range - D3 (10 l/h mini - 3 m³/h maxi) -						3/4" M BSP- NPT Ø 20 x 27 mm							
D 3 RE 3000	0.03 - 0.3	[1:3000 - 1:333]	0.003	9	0.3 - 6	■	●	▲	■	▲	▲	▲	■
D 3 RE 2	0.2 - 2	[1:500 - 1:50]	0.02	60	0.3 - 6	■	●	■	■	★	▲	■	■
D 3 RE 5	0.5 - 5	[1:200 - 1:20]	0.05	150	0.3 - 6	■	●	■	■	★	▲	■	■
D 3 RE 10	1 - 10	[1:100 - 1:10]	0.1	300	0.3 - 6	■	●	■	■	★	▲	■	■
D 3 RE 25 IE ⁽¹⁾	5 - 25	[1:20 - 1:4]	0.5	500	0.3 - 4	■	●	▲	■	▲	▲	▲	■
4.5 m³/h range (100 l/h mini - 4.5 m³/h maxi) -						1"1/4 M BSP Ø 33 x 42 mm							
D 45 RE 3000	0.03 - 0.1	[1:1000 - 1:3000]	0.03	4.5	0.5 - 5	■	●	▲	■	■	▲	▲	●
D 45 RE 1.5	0.2 - 1.5	[1:500 - 1:66]	0.2	67.5	0.5 - 5	■	●	■	■	▲	■	▲	●
D 45 RE 3	0.5 - 3	[1:200 - 1:33]	0.5	135	0.5 - 5	■	●	▲	■	■	■	▲	●
D 45 RE 8	3 - 8	[1:33 - 1:12.5]	3	360	0.5 - 5	■	●	■	■	▲	■	▲	●
8 m³/h range (500 l/h mini - 8 m³/h maxi) -						1"1/2 M compression fittings Ø 40 x 49 mm							
D 8 RE 2	0.2 - 2	[1:500 - 1:50]	1	160	0.15 - 8	■	●	★	★	★	★	★	■
D 8 RE 5	1 - 5	[1:100 - 1:20]	5	400	0.15 - 8	■	●	★	★	★	★	★	■
Gamme 20 m³/h (1m³/h mini - 20 m³/h maxi) -						2" M compression fittings Ø 50 x 60 mm							
D 20 S	0.2 - 2	[1:500 - 1:50]	2	400	0.12 - 10	■	●	▲	▲	▲	▲	▲	●

Each D20S comes with a Kit of legs and this option is also available for the D8 (not necessary for the other ranges)

⁽¹⁾2 m³/h limit